

C13PE ECONOMY SMALL PUSH SAW

FAST ENOUGH TO GET
YOU ON AND OFF THE JOB
TOUGH ENOUGH TO LAST!

Rental equipment has to withstand any and all conditions by user and application. For that reason, the Norton Clipper C13PE suits any rental fleet that both the novice and expert will appreciate to hold-up through tough situations.

The 18" blade guard, ride-on water system and quick-release blade guard lock all keep safety in mind while the rugged frame, powerful engine and easy-to-use console makes cutting a breeze.

KEY APPLICATIONS

GENERAL SLAB CUTTING | CURB CUTTING |
PATCH WORK EXPANSION | JOINT CUTTING | TRENCHING

REDEFINING
JOBSITE MUSCLE[™]





FAST RELEASE GUARD

The quick release pull pin keeps the blade guard locked down for safety during operation. No more jam nuts or tools needed - just pull and lift.



TOUGH FRAME AND RAISED AXLE

Thick, heavy-duty gauge metal frame endures the hardest of users and jobsites. Resists twisting for a tried and true straight cut.



UNCOMPLICATED CONTROL PANEL

Everything at your fingertips to manage the saw with ease: depth locking mechanism, emergency shut off and water valve within easy reach.

TECHNICAL SPECIFICATIONS

	C13PE
Product Number	701846 47524 2
Blade Guard Capacity - in (mm)	18" (457)
Maximum Depth of Cut - in (mm)	6-5/8" (168)
Arbor Size - in (mm)	1" (25.4)
Blade Flange Diameter - in (mm)	4-1/2" (114)
Blade Shaft RPM	2,750
Blade Shaft Diameter - in (mm)	1.00" (25.4)
Blade Shaft Bearings	Heavy Duty Pillow Block
Blade Shaft Drive	3 Belts
Blade Guard Attachment	Pivoting, All Steel
Blade Control	Hand Wheel/Screw Feed
Axle - Front - in (mm)	.75" (19)
Axle - Rear - in (mm)	.75" (19)
Wheels - Front - in (mm) D x W x B	4"x1.5"x.75" (102x38x19)
Wheels - Rear - in (mm) D x W x B	8"x2.50"x.75" (203x64x19)
Handle Bars/Adjustment Length - in (mm)	-NA-
Water Tank Capacity - gal (l)	-NA-
Control	Push
Chassis	Heavy Duty Box Design
Power Source	Gasoline, Single Cylinder 4 Cycle
Motor/Engine Type	Honda GX390
Specifications	GX390K1QXC9
Maximum Horsepower*	13 HP (9.5 kW)
Net Horse Power*	11 HP (8.2 kW)
Displacement - cu In (l)	23.7 cu in (0.39 l)
Bore - in (mm)	3.5" (88)
Stroke - in (mm)	2.5" (64)
Cylinders/Cycle	Single Cylinder 4 Cycle
Fuel Capacity - gal (l)	1.79 gal. (6.5 l)
Oil Capacity - qt (l)	1.16 qt. (1.1 l)
Air Filter	Four Stage Cyclone
Starter	Manual
Engine Cooling	Forced Air

SAW DIMENSIONS

	C13PE
Height - in (mm)	38-13/16" (986)
Minimum Saw Length (Transport) - in (mm)	42-3/4" (1086)
Maximum Saw Length (Working) - in (mm)	63" (1600)
Maximum Pointer Length - in (mm)	20" (508)
Frame Width - in (mm)	16-1/2" (419)
Saw Width - in (mm)	21-27/64" (544)
Front (Outside to Outside Wheel Width) - in (mm)	14-17/32" (369)
Rear (Outside to Outside Wheel Width) - in (mm)	19-9/32" (490)
Blade to Wall - in (mm)	1-23/32" (44)
Wheel Base Length - in (mm)	15-3/4" (400)
Weight - uncrated - lbs (kg)	220 (100 kg)

*= Data Provided by Motor/Engine Manufacturer

REDEFINING
JOBSITE MUSCLE™

www.facebook.com/NortonAbrasivesNA | www.youtube.com/NortonAbrasives | www.nortonabrasives.com

USA CUSTOMER SERVICE:

Toll Free Phone: 1 (800) 554-8003
Toll Free Fax: 1 (800) 443-1092

CANADA CUSTOMER SERVICE:

Toll Free Phone: 1 (800) 263-6565
Toll Free Fax: 1 (800) 561-9490

FORM #8386 REV. 08/19

© Saint-Gobain August 2019

Norton Clipper and "Reshaping Your World" are registered trademarks; "Redefining Jobsite Muscle" is a trademark of Saint-Gobain Abrasives.