

PART NUMBER

Norton Brushable Seam Sealer

076607**82746**

PACKAGE SIZE

1 Quart Can

DESCRIPTION

Norton Brushable Seam Sealer is a rapid curing flexible seam sealer designed for all types of painted surfaces, bare metal and primed surfaces. It is resistant to weather exposure and temperature variations. A brush grade sealant used to seal any body seam against moisture or dust. Skins in 5 minutes; paintable in 30. Use on flat seams in trunk areas or to finish skin panels. Can hold brush marks for OEM appearance. Excellent toolability.



APPLICATION

1. Clean surface with Norton Panel and Adhesive Cleaner (076607**82780**)
2. Sand with 80 grit
3. Norton Brushable Seam Sealer can be applied with an acid brush, or by using the cartridge container and a standard caulking gun
4. Excess may be cleaned with Norton Panel and Adhesive Cleaner (076607**82780**)

SUBSTRATES

Bare Steel, Bare Galvanized, Bare Aluminum, Primer- Self-Etch, 1K, 2K

TECHNICAL DATA

WORK TIME: 1 to 3 Minutes
 PAINT TIME: 30 Minutes
 MIXING: Ready to Use
 APPEARANCE: Gray
 SHELF LIFE: 1 Year

REGULATORY

CATEGORY: SEALANT			
VOC Actual	<3.25 lb/gal (390 g/l)	Weight % of Exempt Compounds	0
VOC Regulatory	<3.25 lb/gal (390 g/l)	Volume % of Exempt Compounds	0
Weight % Volatiles	28.0 to 32.0%	Density of Material #/gal	9.9 to 10.1 lb/gal
Weight % of Water	0		

PRECAUTIONS

For use only by professional use only. Before use, read and follow all TDS, label and SDS precautions.