



## PART NUMBER

Norton Rubberized Undercoat

076607**82776**

## PACKAGE SIZE

20 oz. Can/16 oz. Net Weight

6/Case

## DESCRIPTION

Seals out rust, fumes, heat and cold while protecting underbody areas. Excellent adhesion that won't crack or chip under normal conditions. Engineered to protect underbody areas from moisture and abrasion while deadening sound. Fast drying and economical.

## APPLICATION

1. Shake well
2. Clean surface with Norton Panel and Adhesive Cleaner (076607**82780**)
3. Holding can 8- 10 inches from surface, apply 2- 3 light even coats. Short, even strokes will produce best results
4. Remove overspray with Norton Panel and Adhesive Cleaner (076607**82780**)
5. When finished, invert can and spray until valve is free of material to prevent clogging

**IMPORTANT:** On cars equipped with catalytic converters, exhaust components operate at temperatures exceeding 1000°F (520°C). Therefore, avoid application of undercoating and/ or rust proofing materials within 12" of the exhaust system.

## SUBSTRATES

Painted or Primed Steel, Bare Steel, Aluminum Wheel Wells, Galvanized Steel, Frame Rails, Bare Aluminum

## TECHNICAL DATA

MIXING: Ready to spray

APPEARANCE: Black

SHELF LIFE: 1 Year

## REGULATORY

### CATEGORY: UNDERCOAT

VOC Content: <40% by weight



## PRECAUTIONS

For professional use only. Before use, read and follow all TDS, label and SDS precautions.



FORM # 8743-82776 REV. 08/19

© Saint-Gobain August 2019.

Norton is a registered trademark of Saint-Gobain Abrasives.