



REPORT CARD

All testing done by 3rd party

Performance						
Test type	Test description	ASTM	PolyWhey® 3500 satin	Bona Traffic® satin w/crosslinker	Basic StreetShoe® 275 satin w/crosslinker	Pallmann X-98 sating w/crosslinker
Taber performance	How localized abrasion wears through a coating	ASTM D 4060/AC-04-09 rev1	< 1% loss	< 1% loss	< 1% loss	< 1% loss
Black heel mar	How a coating resists discoloration and damage from daily foot traffic	ASTM 5170/AC-04-18 rev 2	5 out of 5 (5 is highest)	2	3	N/A
Scuff mar	How weight and grit will reduce sheen and film thickness	ASTM 5170/AC-04-18 rev 2	5 out of 5 (5 is highest)	4	3	N/A

Safety and Value				
Characteristic	PolyWhey® 3500 satin	Bona Traffic® w/crosslinker	Basic StreetShoe® 275 satin w/crosslinker	Pallmann X-98 w/crosslinker
VOC in grams per liter	95	210	250	250
Whey Technology	Yes	No	No	No
Contains mutagen NMP	No	No	No	Yes
Contains OHSA regulated isocyanate in crosslinker	No	Yes	No	No
Renewable content	Yes	No	No	No
No waste single component	Yes	No	No	No
Coverage	600-700	350-400	550-700	450-500
Cost per square foot	\$.18	\$.28	\$.14	\$.24

Vermont Natural Coatings, Inc.

P.O. Box 512 190 Junction Road Hardwick, Vermont 05843 (802) 472-8700 Fax: (802) 472-8755

vermontnaturalcoatings.com