



MANUAL TILE CUTTERS CTM 640 / CTM 935 / CTM 1200





MANUAL TILE CUTTERS **CTM 1200** CTM 640 & CTM935 • Robust and precise guide rail 15 x 40 mm • Precise 38x8 mm monorail guide • Powder-coated, reinforced base plate Adjustable 0-45° angle stop Double crushing device for normal and diagonal Specially designed for straight and diagonal cutting cuts (0-45°) Features a Tungsten Carbide cutting wheel that is • Featuring Tungsten Carbide wheels, ideal for ideal for porcelain and stoneware cutting porcelain tiles and stoneware • Lateral extension arms for large format spring Spring-loaded support surface on both sides steel plates allowing better stability during use Recesses in the base plate make the cutter • Lateral extension arms to accommodate large lightweight format panels • Specially designed base plate for optimal weight

distribution



PRODUCT DATA	CTM 640	CTM 935	CTM 1200
Item No	70184607906	70184607907	70184607908
EAN 13 Code	5450248765790	5450248765806	5450248765813
Max. cutting length (mm)	640	935	1200
Max. diagonal cut tile (mm)	450 x 450	660 x 660	840 x 840
Cutting thickness min - max(mm)	3 - 15	3 - 15	3 - 20
Weight (kg)	11,40	14,25	30,95

ACCESSORIES INCLUDED / CONSUMABLE

	ITEM NO.	EAN 13 CODE
Scoring wheel CTM 640 - CTM 935 (ø18mm)	310534515	5450248770299
Scoring wheel CTM 1200 (ø22mm)	310534533	5450248770374



Scoring wheel



ACCESSORIES OPTIONNAL

DESCRIPTION	ITEM NO.	EAN 13 CODE	UTILIZATION
	GLUE AND JOIN	T PREPARATION	
1 - Mixer 120x600mm Hexa	70184608772	5450248780564	Mixing rod, for mixing glue or adhesive mortar using a hexagonal chuck drill
2 - Mixer 120x600mm M14	70184608773	5450248780571	Mixing rod, for mixing glue or adhesive mortar using an M14 connection mixer
	TIL	ING	
3 - 250 Clips 1,5mm for 3-12 mm	70184608775	5450248780595	Self-leveling spacers, are used to adjust the distance between the tiles and to put the tiles perfectly level using self-leveling shims. For 1.5mm thick joints and 3-12mm thick tiles
4 - 250 Clips 1,5mm for 12-28 mm	70184608778	5450248780625	Self-leveling braces, are used to adjust the distance between the tiles and to put the tiles perfectly level using self-leveling shims. For 1.5mm thick joints and 12 to 28mm thick tiles
5 - 100 Wedges 0 to 12mm	70184608774	5450248780588	Reusable self-leveling shims, used to level all tiles, thickness from 0 to 12mm
6 - Adjustable plier PINCE	70184608776	5450248780601	Pliers for self-leveling system, used to insert the self-leveling shims into the self-leveling braces
7 - Self-leveling Basisset	70184608777	5450248780618	Self-leveling kit, consisting of all the accessories for installing tiles in the rules of the art. In this kit you will find: 1 clamp, 100 self-leveling braces for 1.5 mm thick joints for tiles from 3 to 12 mm thick and 100 self-leveling wedges
8 - Rubber hammer white 60 mm	70184608779	5450248780632	Rubber mallet size 2 Ø60mm to adjust the laying of the tiles
9 - Knee Pads Standard	70184608769	5450248780533	Foam knee pads for indoor and outdoor
	INSTALLATION (OF TILING JOINT	
10 - Tile layer´s hawk 280x140mm black	70184608765	5450248780496	Foam grouting trowel, for filling tile joints, ideal for large surfaces, vertical work and wide joints
11 - Grout Flat 255x95mm strong	70184608767	5450248780519	Epoxy grout trowel, for filling Silicone / Epoxy tile joints, ideal for large surfaces, vertical work and wide joints
12 - Spreader, wooden handle 180mm	70184608770	5450248780540	Rubber squeegees are used for filling tile joints
13 - Spreader, wooden handle 300mm	70184608771	5450248780557	Rubber squeegees are used for filling tile joints

DESCRIPTION	ITEM NO.	EAN 13 CODE	UTILIZATION
	JOINT AND TILE	CLEANING	
i - Tile cleaner 280x140mm Hydro	70184608766	5450248780502	Foam float, used to clean the tile and excess joint paste, ideal tool with the roller cleaning bucket
5 - Grouting sponge, Hydro 170x115x70 mm	70184608768	5450248780526	Hydro sponge, is used to clean th tiles and the excess paste attache
6 - Tile washing set 24 L + Rollers	70184608780	5450248780649	24L rinsing tank, for cleaning tile joints on large surfaces, designed to drain the foam float
2		3	4 AMOUNTE DE LA CONTRACTOR DE LA CONTRAC



























Saint-Gobain Abrasifs European Headquarters Rue de l'Ambassadeur - B.P.8 78 702 Conflans Cedex France

Tel: +33 (0)1 34 90 40 00 Fax: +33 (0)1 39 19 89 56 www.nortonabrasives.com www.youtube.com/NortonAbrasivesEMEA

Norton is a registered trademark of Saint-Gobain Abrasives. Form #4044

