

MAXIMUM POWER FOR MAXIMUM PRODUCTIVITY

WALK-BEHIND 35HP GAS MID-RANGE SELF-PROPELLED SAWS

The 35HP engine has never been better since the introduction of the V-Twin air-cooled Vanguard engine. The strong gasoline engine mounted on a clean, uncomplicated frame makes the C35 series the best choice for small to mid-size applications. Packed with features for maximum performance, our operator-friendly design makes handling and preventative maintenance easier. The C35 series is an ideal saw for contractor work.

REDEFINING
JOBSITE MUSCLE

NORTON

SAINT-GOBAIN

clipper®

WALK-BEHIND 35HP GAS
MID-RANGE SELF-PROPELLED SAWS**Oil Bath Blade Shaft**

Sealed oil bath blade shaft eliminates the daily greasing and provides long hours of operation.

**Powerful 35HP Gasoline Engine**

The Vanguard, Big Block, V-Twin 35HP commercial gasoline engine is smooth and powerful, with proven performance.

**Easy Operating Console**

Simple, user-friendly layout increases operator productivity.

Technical Specifications

PRODUCT #	C3526SS	C3530SS
UPC	701846 42466	701846 42467
Blade Guard Capacity – in (mm)	26" (660)	30" (762)
Maximum Depth of Cut – in (mm)	9-1/2" (241)	12-1/2" (318)
Arbor Size – in (mm)	1" (25.4)	1" (25.4)
Blade Flange Diameter – in (mm)	5" (127)	5" (127)
Blade Shaft RPM	1,900	1,900
Blade Shaft Diameter – in (mm)	1-7/16" (37)	
Blade Shaft Bearings	Heavy Duty Pillow Block	
Blade Shaft Drive	7 Belts	
Blade Guard Attachment	Quick Detach Bayonet	
Blade Control	Electric	
Axle – Front – in (mm)	1" (25.4)	
Axle – Rear – in (mm)	1" (25.4)	
Wheels – Front D x W x B – in (mm)	6" x 2-1/2" x 1" (152 x 64 x 25)	
Wheels – Rear D x W x B – in (mm)	8" x 2-1/2" x 1" (203 x 64 x 25)	
Handle Bars/Adjustment Length – in (mm)	32-1/2" (826)	
Transmission	Eaton Hydrostatic	
Rear End/Differential	Enclosed Gears	
Control	Forward/Reverse Control, Engage/Disengaged Controls	
Speed	0-220 FPM (Forward) 0-100 FPM (Reverse)	
Chassis	Heavy Duty jig-welded box frame	
Power Source	Gasoline, 2 Cylinders 4 Cycle	
Engine Type	Briggs Vanguard	
Specifications	61347701710	
Maximum Horsepower*	35 HP (26kw)	
Displacement – cu In (l)	60.6 cu in (0.993 l)	
Bore – in (mm)	3.366" (85.5)	
Stroke – in (mm)	3.406" (86.5)	
Cylinders/Cycle	2 Cylinders 4 Cycle	
Fuel Capacity – gal (l)	5 gal (18.9 l)	
Oil Capacity – qt (l)	2.5 qt. (2.4 l)	
Air Filter	Three Stage	
Starter	Electric	
Engine Cooling	Air	
SAW DIMENSIONS		
Height – in (mm)	42" (1,069)	42" (1,069)
Minimum Saw Length (Transport) – in (mm)	49-1/2" (1,257)	49-1/2" (1,257)
Maximum Saw Length (Working) – in (mm)	109-3/4" (2,788)	109-3/4" (2,788)
Maximum Pointer Length – in (mm)	33-3/4" (857)	33-3/4" (857)
Frame Width – in (mm)	22-1/2" (572)	22-1/2" (572)
Saw Width – in (mm)	29" (737)	29" (737)
Front (Outside to Outside Wheel Width) – in (mm)	19" (483)	19" (483)
Rear (Outside to Outside Wheel Width) – in (mm)	22-3/4" (578)	22-3/4" (578)
Blade to Wall – in (mm)	1-13/16" (46)	1-13/16" (46)
Wheel Base Length – in (mm)	20-1/4" (514)	20-1/4" (514)
Weight Crated – lbs (kg)	750 (341)	750 (341)
Weight Uncrated – lbs (kg)	650 (295)	650 (295)
ACCESSORIES		
	UPC	SMART PART #
20" Blade Guard	701846 43382	246006
26" Blade Guard	701846 44384	246218
30" Blade Guard	701846 44385	246219
Light Kit w/magnetic base	701846 47436	170304
Water Pump Kit	701846 45877	246292

*= DATA PROVIDED BY MOTOR/ENGINE MANUFACTURER

REDEFINING
JOBSITE MUSCLE™

www.facebook.com/NortonAbrasivesNA | www.youtube.com/NortonAbrasives | www.nortonabrasives.com

USA CUSTOMER SERVICE:

Toll Free Phone: 1 (800) 554-8003
Toll Free Fax: 1 (800) 443-1092

CANADA CUSTOMER SERVICE:

Toll Free Phone: 1 (800) 263-6565
Toll Free Fax: 1 (800) 561-9490

FORM #8847 REV. 01/22

© Saint-Gobain January 2022.

Norton, Norton Clipper, "Redefining Jobsite Muscle", and "Transforming surfaces...and beyond" are trademarks of Saint-Gobain Abrasives. All other trademarks are the property of their respective owners.

