



BBC SERIES BLOCKBUSTER COMPACT PORTABLE MASONRY SAWS

THE BBC SERIES MASONRY SAWS COMBINE THE PERFORMANCE OF A FULL SIZE MASONRY SAW WITH THE CONVENIENCE OF PORTABILITY.

- Available in gas or electric versions
- A rugged jig-welded frame, durable enough for even the heaviest work load
- Stay level blade guard for full depth of cut
- The extended length and open back of water pan design make easier rip cutting of larger masonry materials
- Unique design of tilt-locking cart wheels keeps conveyor in place with less shifting and smoother push/pull
- Integrated forklift brackets for easy loading, unloading, and movement around the work site
- Standard rear wheel dolly design and removable legs make transport and set-up easy




REDEFINING
JOBSITE MUSCLE

TECHNICAL SPECIFICATIONS	BBC157	BBC207	BBC307	BBC547	BBC507
Product Number	701846 82488 0	701846 82501 6	701846 30011 7	701846 82175 9	701846 30012 4
Blade Guard Capacity – in. (mm)	14" (177)	14" (177)	20" (508)	14" (177)	20" (508)
Maximum Depth of Cut – in. (mm)	5" (127)	5" (127)	8" (203)	5" (127)	8" (203)
Arbor Size – in. (mm)	1" (25)	1" (25)	1" (25)	1" (25)	1" (25)
Blade Flange Diameter – in. (mm)	4" (107)	4" (107)	4" (107)	4" (107)	4" (107)
Blade Shaft RPM	2,900	2,900	2,400	2,900	2,400
Blade Shaft Bearings	1" Heavy Duty Flange				
Blade Shaft Drive	1 Belt				
Blade Guard Attachment	All Steel, Stay Level				
Conveyor Cart	All steel cart, tilt-lock cart wheels, anti-skid surface, measuring rule; 45°/90° cutting guide				
Frame	Heavy-duty, jig-welded steel frame. Open construction for larger materials. Adjustable foot pedal and head height control.				
Water Pump	Electric or Mechanically Belt Driven	Electric or Mechanically Belt Driven	Electric or Mechanically Belt Driven	Mechanically Belt Driven	Mechanically Belt Driven
Power Source	Electric	Electric	Electric	Gasoline	Gasoline
Motor/Engine Type	Baldor	Baldor	Baldor	Honda GX200	Honda GX200
Specifications	T.E.F.C., Thermal Protection	T.E.F.C., Thermal Protection	T.E.F.C., Thermal Protection	GX200K1QXC9	GX200K1QXC9
Net Horsepower*	1-1/2 HP	2 HP	3 HP	5.5 HP (4.1 kW)	5.5 HP (4.1 kW)
Voltage	115/230 volts	115/230 volts	208-230 volts	NA	NA
Cycle*/Current/Phase	60 Hz/AC/1	60 Hz/AC/1	60 Hz/AC/1	NA	NA
Full Load Amps	13.4/6.7 Amps	16.8/8.4 Amps	13 Amps	NA	NA
Starter	Capacitor	Capacitor	Capacitor	Recoil	Recoil
Engine Cooling	Air	Air	Air	Forced Air	Forced Air
Displacement – cu. In (l)	NA	NA	NA	11.96 cu. In (0.196 l)	11.96 cu. In (0.196 l)
Bore – in. (mm)	NA	NA	NA	2.7" (68)	2.7" (68)
Stroke – in. (mm)	NA	NA	NA	2.12" (54)	2.12" (54)
Cylinders/Stroke	NA	NA	NA	Single Cylinder 4 Cycle	Single Cylinder 4 Cycle
Fuel Capacity – gal. (l)	NA	NA	NA	.95 gal. (3.6 l)	.95 gal. (3.6 l)
Oil Capacity – qt. (l)	NA	NA	NA	.63 at. (.6 l)	.63 at. (.6 l)
Air Filter	NA	NA	NA	Four Stage Cyclone	Four Stage Cyclone
SAW DIMENSIONS					
Saw Length – in. (mm)	60" (1,524)	60" (1,524)	60" (1,524)	60" (1,524)	60" (1,524)
Saw Width – in. (mm)	24" (609)	24" (609)	24" (609)	24" (609)	24" (609)
Saw Height – in. (mm)	34" (864)	34" (864)	34" (864)	38" (965)	38" (965)
Maximum Arbor Height Over Table – in. (mm)	24-1/2" (623)	24-1/2" (623)	24-1/2" (623)	24-1/2" (623)	24-1/2" (623)
Cart Length – in. (mm)	16" (404)	16" (404)	16" (404)	16" (404)	16" (404)
Cart Width – in. (mm)	19-3/8" (492)	19-3/8" (492)	19-3/8" (492)	19-3/8" (492)	19-3/8" (492)
Pan Length – in. (mm)	39-3/8" (1,000)	39-3/8" (1,000)	39-3/8" (1,000)	39-3/8" (1,000)	39-3/8" (1,000)
Pan Width – in. (mm)	18-1/8" (460)	18-1/8" (460)	18-1/8" (460)	18-1/8" (460)	18-1/8" (460)
Weight Crated – lbs (kg)	280 (127)	280 (127)	280 (127)	305 (138)	305 (138)
Weight Uncrated – lbs (kg)	250 (113)	250 (113)	250 (113)	275 (125)	275 (125)
ACCESSORIES					
	UPC	SMART PART #			
Electric Water Pump - PE-1	701846 68392 0	214169			
BBC Mechanical Water Pump	003100 04237 8	072305			
BBC Water Pump Pulley	003100 04669 9	075270			
Conveyor Cart Replacement	003100 07367 7	083754			

*= Data Provided by Engine Manufacturer

Genuine Norton diamond blade included with saw.



Electric Water Pump



Conveyor Cart Replacement

**REDEFINING
JOBSITE MUSCLE™**

www.facebook.com/NortonAbrasivesNA | www.youtube.com/NortonAbrasives | www.nortonabrasives.com

USA CUSTOMER SERVICE:

Toll Free Phone: 1 (800) 554-8003
Toll Free Fax: 1 (800) 443-1092

CANADA CUSTOMER SERVICE:

Toll Free Phone: 1 (800) 263-6565
Toll Free Fax: 1 (800) 561-9490

FORM #7736 REV. 01/22

© Saint-Gobain January 2022.

Norton, Norton Clipper, "Redefining Jobsite Muscle" and "Transforming surfaces...and beyond" are trademarks of Saint-Gobain Abrasives. All other trademarks are the property of their respective owners.

