

ADVANTAGES OVER TRADITIONAL CLAY BARS Removability Industrial Tool **Durability Washable** Reshape **Brake Dust Rail Dust Pollution Overspray FAST FAST FAST SLOW SLOW SLOW SLOW**



PUT YOUR





Use ONLY on clean, cool surfaces. Adequate lubrication is critical to the application and water is NOT an acceptable lubricant.



Step 1

Thoroughly wash and rinse vehicle free of dirt and debris. Remove any tar and/or grease prior to application.



Step 2

Mist sufficient lubricant onto the surface evenly.



Step 3

Polish the surface with REVvive BY RSG Contaminate Eliminator Pad using light pressure using REVvive by RSG Hand Strap, Dual Action Tool or Hand.



Step 4

Wipe off residue.



















An Initiative of Saint-Gobain

www.refinishsolutionsgroup.com | 1 (800) 456-8444 | Email: rsg@saint-gobain.com

FORM #8946 REV. 09/22

© Saint-Gobain September 2022.

Carborundum, Farécla, Norton, Solar Gard, REVvive by RSG, and "Refinish Solutions Group" are trademarks of Saint-Gobain Abrasives. All other trademarks are the property of their respective owners. Vehicle image provided courtesy of Ford Motor Company.